edu.mit.csail.aeolus.api
Class AeolusClosure

```
java.lang.Object
  └ edu.mit.csail.aeolus.api.AeolusClosure
```

All Implemented Interfaces:
AeolusSafe

```
public abstract class AeolusClosureextends java.lang.Objectimplements AeolusSafe
```

This class is used to create share-able executable objects in Aeolus. The closure includes the labels specified by the creator of the closure.

Field Summary

EventID	**closureLastEid** **Deprecated.**

Constructor Summary

protected	**AeolusClosure**(PID pid) Construct a closure that will run with the authority of pid

Method Summary

java.util.ArrayList<java.lang.Integer>	**getBasisCopy**() **Deprecated.**
PID	**getPID**() Return the PID associated with the closure

Methods inherited from class java.lang.Object
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

closureLastEid

```
@Deprecated public EventID closureLastEid
```

Deprecated.

Constructor Detail

AeolusClosure

```
protected AeolusClosure(PID pid)
                 throws AuthorityException
```

Construct a closure that will run with the authority of pid

Throws:

`AuthorityException` - - if caller's thread doesn't actFor pid

Method Detail

getBasisCopy

```
@Deprecated public final java.util.ArrayList<java.lang.Integer> getBasisCopy()
```

Deprecated.

---

getPID

```
public final PID getPID()
```

Return the PID associated with the closure

Returns:

the PID associated with the closure